

05-15-00

A

The Law Offices of  
**STRAUB & POKOTYLO**

Michael P. Straub  
 mike@sp-ip.com

John C. Pokotylo  
 john@sp-ip.com

1 Bethany Road  
 Suite 56, Bldg. 4  
 Hazlet, NJ 07730

Telephone: 732-335-1222  
 Facsimile: 732-335-1228  
 Internet Site: www.sp-ip.com

May 24, 2000

**UTILITY PATENT APPLICATION TRANSMITTAL LETTER**

Assistant Commissioner of Patents  
 Box **Patent Application**  
 Washington, D.C. 20231

Sir:

Enclosed herewith for filing is the following  
**utility patent application:**

Attorney Docket No.: **OOCL-29(3TS-00S0338)**

Applicant: **Kenro OHSAWA**

Title: **"COLOR REPRODUCTION SYSTEM"**

**PATENT APPLICATION FILING FEE CALCULATION**

	<u>No. Filed</u>	<u>Less</u>	<u>Rate/Claim</u>	<u>Fee</u>
Total				
Claims	<u>14</u>	-20	0 x \$18.00	\$ 00.00
Independent				
Claims	<u>3</u>	-3	0 x \$78.00	\$ 00.00
			Minimum Filing Fee	\$ 690.00
			Multiple Dependency Fee	
			(if applicable - \$260.00)	\$ 00.00
			50% Reduction for Small Entity	
			(Independent Inventor, Non-profit	
			Corporation, or Small Business	
			Concern) - appropriate	
			verified statement attached	\$- 00.00
			TOTAL FILING FEE	\$ 690.00
			ASSIGNMENT RECORDATION	\$ 40.00
			<b>TOTAL FEES ENCLOSED</b>	<b>\$ 730.00</b>

JC816 U.S. PTO  
 05/24/00

JC584 U.S. PTO  
 09/577445  
 05/24/00

05/24/00 09/577445 JC584 U.S. PTO

- ☒ Specification: 41 Total Pages (including claims and abstract)
- ☒ Drawing(s): 3 Total Sheets (FIGs. 1-7)

Also enclosed herewith for filing in connection with the enclosed application are:


- ☒ Our check in the amount of \$ 730.00 (the total filing fee) is enclosed herewith. If this check is unacceptable, insufficient or omitted, kindly charge the entire or additional filing fee, as appropriate, to the deposit account of **Straub & Pokotylo**, deposit account number **50-1049**. To facilitate that charge, a duplicate copy of this letter is enclosed herewith.
- ☒ Postcard Receipt;
- ☐ Preliminary Amendment;
- ☒ Oath or Declaration:  
☒ Newly executed on May 17, 2000;  
☐ Copy from a prior application (36 C.F.R. § 1.63(d));
- ☒ Assignment Papers to: Olympus Optical Co., Ltd.;
- ☐ Information Disclosure Statement, modified PTO-1449, and (1) cited reference(s);
- ☐ Letter referencing previously filed disclosure document; number \_\_\_\_\_ filed \_\_\_\_\_;
- ☐ Verified Statement Claiming Small Entity Status:  
☐ Newly executed on \_\_\_\_\_;  
☐ Copy from a prior application, status still proper and desired;
- ☐ Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. §§ 1.63(d)(2) and 1.33(b);
- ☐ Microfiche Computer Program (Appendix);
- ☐ English translation document;

☒ Submission of Priority Document and a certified copy of a Japanese patent application or inventor's certificate, filed May 25, 1999 and assigned serial no. 11-144932, upon which a claim to priority is made; and

☐ Other: \_\_\_\_\_  
\_\_\_\_\_.

Respectfully submitted,


STRAUB & POKOTYLO

  
\_\_\_\_\_  
John C. Pokotylo, Attorney  
Reg. No. 36,242  
Customer No. IDON601137

\*\*\*EXPRESS MAIL CERTIFICATION\*\*\*

"Express Mail" mailing label number: EL547453223US  
Date of deposit: May 24, 2000

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner of Patents, **Box Patent Application**, Washington, D.C. 20231.

  
\_\_\_\_\_  
Signature of person making certification

John C. Pokotylo  
\_\_\_\_\_  
Name of person making certification

TITLE OF THE INVENTION

COLOR REPRODUCTION SYSTEM

CROSS-REFERENCE TO RELATED APPLICATIONS

5 This application is based upon and claims the benefit of priority from the prior Japanese Patent Application No. 11-144932, filed May 25, 1999, the entire contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

10 The present invention relates to a reproduction system having a color image processing apparatus for calculating tristimulus values under observation illumination light corresponding to the spectral reflectance of an object.

15 In recent years, color management systems (CMS) for matching the colors of input/output images between a plurality of color image devices such as a color CRT monitor and color printer are becoming popular in various fields handling color images.

20 In a CMS, a problem is arisen in accurately reproducing colors to be perceived when sensing illumination light in sensing an object is different from observation illumination light in observing an image obtained by displaying image data obtained by  
25 sensing on a CRT monitor or outputting it by a printer because the colors of the observed image are different between these environments due to the change in human

visual characteristics.

As a solution to this problem, a color reproduction method is employed in which the spectral reflectance  $f(\lambda)$  of the object is obtained, and CIE XYZ values of the reflectance spectrum are calculated by multiplying the spectral reflectance by the spectrum  $E_o(\lambda)$  of observation illumination light for display.

The spectral reflectance  $f(\lambda)$  is obtained in correspondence with each pixel of the object image obtained by sensing the object. The CIE XYZ values are calculated by equations (1) using XYZ color matching functions  $x(\lambda)$ ,  $y(\lambda)$ , and  $z(\lambda)$  defined by the International Commission on Illumination (CIE).

$$X = \int_{\lambda=380}^{780} x(\lambda)E_o(\lambda)f(\lambda)d\lambda$$

$$Y = \int_{\lambda=380}^{780} y(\lambda)E_o(\lambda)f(\lambda)d\lambda$$

$$Z = \int_{\lambda=380}^{780} z(\lambda)E_o(\lambda)f(\lambda)d\lambda$$

where  $\lambda$  is the wavelength [nm]. In this method of obtaining the spectral reflectance  $f(\lambda)$  corresponding to each pixel of the object image and calculating the XYZ values under the observation illumination light on the basis of the spectral reflectance for display, the XYZ values when the object is present under the observation illumination light are displayed. For this reason, accurate colors to be perceived can be

reproduced without using a visual model for chromatic adaptation.

In the above-described conventional color reproduction system, to calculate the XYZ values under the observation illumination light from the spectral  
5 reflectance  $f(\lambda)$  of the object, the spectrum  $E_o(\lambda)$  of the observation illumination light must be obtained.

However, to accurately measure the spectrum, a measurement instrument such as a spectrophotometer is  
10 necessary. Since spectrophotometers must be prepared at various observation positions to measure the spectrum of the observation illumination light  $E_o(\lambda)$ , resulting in cumbersomeness.

#### BRIEF SUMMARY OF THE INVENTION

15 It is an object of the present invention to provide a color reproduction system having a color image processing apparatus for calculating tristimulus values under observation illumination light corresponding to the spectral reflectance of an object  
20 without using any measurement instrument such as a spectrophotometer, unlike the prior art.

In order to solve the above problem, as a characteristic feature of the present invention, in a color reproduction system comprising tristimulus value  
25 calculation means for calculating tristimulus values under observation illumination light corresponding to a spectral reflectance of an object, color image signal

calculation means for calculating an output color image  
signal on the basis of the tristimulus values, and  
color image output means for outputting a color image  
upon receiving the output color image signal, the  
5 tristimulus value calculation means calculates the  
tristimulus values using spectral reflectance data of  
a color chip formed from a plurality of unit color  
chips, color chip sensing data obtained by sensing the  
color chip with an input device under the observation  
10 illumination light, spectral sensitivity data of the  
input device, and color matching function data.

In the present invention having this arrangement,  
the tristimulus values under the observation illumina-  
tion light corresponding to the spectral reflectance of  
15 the object can be obtained using a color chip having  
a known spectral reflectance and an input device for  
sensing the color chip, which has a known spectral  
sensitivity. That is, the spectral reflectance  
image data can be converted into XYZ image data as  
20 tristimulus values under the observation illumination  
light without using any measurement instrument such as  
a spectrophotometer.

As a characteristic feature of an aspect, the  
tristimulus value calculation means multiplies the  
25 color chip sensing data by a matrix obtained from  
the relationship between the product of the spectral  
reflectance of the object and the color matching

functions and the product of the spectral reflectance of the color chip and the spectral sensitivity of the input device, thereby calculating the tristimulus values.

5           When the product of the spectral reflectance of the object and the color matching functions can be expanded by the product of the spectral reflectance of the color chip and the spectral sensitivity of the input device for sensing the color chip, spectral  
10           reflectance image data can be highly accurately converted into XYZ image data as the tristimulus values under the observation illumination light.

          Even when such expansion is impossible, highly accurate conversion can be performed by increasing the  
15           expansion accuracy by changing the color chip to be used and the characteristics of the input device for sensing the color chip in accordance with the spectral reflectance of the object.

          As a characteristic feature of another aspect,  
20           the tristimulus value calculation means obtains the tristimulus values as the linear sum of basis function tristimulus values obtained by multiplying the color chip sensing data by a matrix obtained from the relationship between the product of the plurality of  
25           basis functions of the spectral reflectance of the object and the color matching functions and the product of the spectral reflectance of the color chip and the



spectral sensitivity of the input device.

When the product of the plurality of basis  
functions of the spectral reflectance of the object and  
the color matching functions can be expanded by the  
5 product of the spectral reflectance of the color chip  
and the spectral sensitivity of the input device for  
sensing the color chip, spectral reflectance image data  
can be highly accurately converted into XYZ image data  
as the tristimulus values under the observation  
10 illumination light.

Even when such expansion is impossible, highly  
accurate conversion can be performed by increasing the  
expansion accuracy by changing the color chip to be  
used and the characteristics of the input device for  
15 sensing the color chip in accordance with the basis  
function of the spectral reflectance of the object.

When all spectral reflectances of the object  
are expanded by the basis functions, the conversion  
accuracy for the actual object can be obtained in  
20 advance by evaluating the conversion accuracy for  
the basis function in advance.

In addition, the tristimulus values under the  
observation illumination light corresponding to the  
basis function of the spectral reflectance of the  
25 object can be calculated in advance. For this reason,  
after the expansion coefficient corresponding to the  
spectral reflectance of the object is input, the

tristimulus values under the observation illumination light corresponding to the spectral reflectance of the object can be calculated at a high speed as the linear sum of the tristimulus values of the basis functions.

5           More specifically, according to the first aspect of the present invention, there is provided a color reproduction system comprising:

          tristimulus value calculation means for calculating  
10           tristimulus values under observation illumination light corresponding to a spectral reflectance of an object, the tristimulus value calculation means calculating the tristimulus values using spectral reflectance data of a color chip formed from a plurality of unit color chips, color chip sensing data  
15           obtained by sensing the color chip with an input device under the observation illumination light, spectral sensitivity data of the input device, and color matching function data;

          means for calculating an output color image signal  
20           on the basis of the calculated tristimulus values; and

          means for outputting a color image on the basis of the output color image signal.

          According to the second aspect of the present invention, there is provided a color reproduction  
25           system comprising:

          first image sensing means for sensing an object under sensing illumination light;

means for calculating a spectral reflectance of  
image data of the object sensed by the first image  
sensing means on the basis of spectral sensitivity data  
of the first image sensing means, spectrum data of the  
5 sensing illumination light, statistic data of a spectra  
reflectance of the object, and color matching function  
data, and outputting spectral reflectance image data  
corresponding to the calculated spectral reflectance;

second image sensing means for sensing a color  
10 chip under observation illumination light;

means for calculating tristimulus values of the  
object under the observation illumination light on the  
basis of the output spectral reflectance image data,  
color chip image data of the color chip sensed by the  
15 second image sensing means, spectral sensitivity data  
of the second image sensing means, color chip spectral  
reflectance data representing a spectral reflectance of  
the color chip, and color matching function data;

means for calculating an output color image signal  
20 on the basis of the calculated tristimulus values; and

means for outputting a color image on the basis of  
the output color image signal.

According to the third aspect of the present  
invention, there is provided a color reproduction  
25 system comprising:

first image sensing means for sensing an object  
under sensing illumination light;

means for outputting expansion coefficient data representing a linear sum of basis functions of a spectral reflectance of the object on the basis of spectral sensitivity data of the first image sensing means, spectrum data of the sensing illumination light, statistic data of a spectral reflectance of the object, and color matching function data;

second image sensing means for sensing a color chip under observation illumination light;

means for calculating tristimulus values of the object under the observation illumination light on the basis of the output expansion coefficient data, color chip image data of the color chip sensed by the second image sensing means, spectral sensitivity data of the second image sensing means, color chip spectral reflectance data representing a spectral reflectance of the color chip, and color matching function data;

means for calculating an output color image signal on the basis of the calculated tristimulus values; and

means for outputting a color image on the basis of the output color image signal.

Additional objects and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The objects and advantages of the invention may be realized and obtained by means of the instrumentalities and

combinations particularly pointed out hereinafter.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate presently preferred embodiments of the invention, and together with the general description given above and the detailed description of the preferred embodiments given below, serve to explain the principles of the invention.

FIG. 1 is a block diagram showing the arrangement of a color reproduction system according to the first embodiment of the present invention;

FIG. 2 is a block diagram showing the arrangement of a spectral reflectance calculation unit of the first embodiment;

FIG. 3 is a block diagram showing the arrangement of a tristimulus value calculation unit of the first embodiment;

FIG. 4 is a block diagram showing the arrangement of a color image signal calculation unit of the first embodiment;

FIG. 5 is a block diagram showing the arrangement of a color reproduction system according to the second embodiment of the present invention;

FIG. 6 is a block diagram showing the arrangement of a spectral reflectance calculation unit of the second embodiment; and

FIG. 7 is a block diagram showing the arrangement of a tristimulus value calculation unit of the second embodiment.

#### DETAILED DESCRIPTION OF THE INVENTION

5           The embodiments of the present invention will be described below with reference to the accompanying drawing.

(First Embodiment)

10           FIG. 1 shows a color reproduction system according to the first embodiment of the present invention.

          When an object 1 is sensed by a first digital camera 3 under sensing illumination light by sensing illumination 2, an object image signal is output from the digital camera 3 as RGB image data. This RGB image data is input to a spectral reflectance calculation unit 4.

          Upon receiving the RGB image data from the digital camera 3, the spectral reflectance calculation unit 4 calculates, as a spectral reflectance  $f(\lambda)$  corresponding to each pixel of the RGB image data, the spectral reflectance  $f(\lambda)$  of the object 1 using the spectral sensitivity data of the digital camera 3, spectrum data of the sensing illumination light, statistic data of the object spectral reflectance, and color matching function data.

          Image data (called spectral reflectance image data) F corresponding to the calculated distribution of

the spectral reflectance  $f(\lambda)$  is output. The spectral reflectance image data F is input to a tristimulus value calculation unit 5.

5 When a color chip 6 is sensed by a second digital camera 8 as an input device under observation illumination light by observation illumination 7, color chip image data P' corresponding to the color chip 6 is output from the digital camera 8.

10 The color chip 6 is formed by arraying a plurality of (M) unit color chips having independent spectral reflectances in a matrix. The color chip 6 is laid out without any illumination variation and sensed by the digital camera 8. The color chip image data P' is input to the tristimulus value calculation unit 5.

15 The tristimulus value calculation unit 5 calculates tristimulus values X, Y, and Z corresponding to the spectral reflectance of the object 1 under the observation illumination light from the spectral reflectance image data F input from the spectral reflectance calculation unit 4, the color chip image data P' input from the second digital camera 8, the spectral sensitivity data of the digital camera 8, the color chip spectral reflectance data representing the spectral reflectance distribution of the color chip 6, 20 and color matching function data, and outputs XYZ image data. 25

The XYZ image data are input to a color image

signal calculation unit 9. The spectral sensitivity  
of the digital camera 8, the color chip spectral  
reflectance, and color matching functions have known  
values and stored and held in the tristimulus value  
5 calculation unit 5 in advance.

The color image signal calculation unit 9 converts  
the XYZ image data input from the tristimulus value  
calculation unit 5 into output color image signals R',  
G', and B' using a monitor profile as input/output  
10 characteristic information of a CRT monitor 10, which  
is obtained in advance by measurement.

The output color image signals R', G', and B' are  
input to the CRT monitor 10 as a color image output  
means whereby an object image having the colors of the  
15 object 1 under the observation illumination light is  
displayed on the CRT monitor 10.

The detailed arrangement and processing of each  
section shown in FIG. 1 will be described next in  
detail.

20 FIG. 2 shows the arrangement of the spectral  
reflectance calculation unit 4.

The spectral reflectance calculation unit 4  
comprises a matrix conversion unit 21, storage unit 22,  
and matrix calculation unit 23.

25 The RGB image data from the first digital camera 3  
is input to the matrix conversion unit 21. The matrix  
conversion unit 21 outputs the spectral reflectance



image data F by multiplying the RGB image data by  
a matrix calculated by the matrix calculation unit 23  
on the basis of data stored in the storage unit 22.

5 The spectral reflectance calculation unit 4  
shown in FIG. 2 will be described in more detail.  
The storage unit 22 stores and holds spectral  
sensitivity data H of the first digital camera 3,  
sensing illumination light spectrum data  $E_m$ , and  
correlation matrix data A of the spectral reflectance  
10 of the object 1 as data at a 1-nm interval in the  
wavelength range of 380 to 780 nm.

The sensing illumination light spectrum data  $E_m$  is  
measured using a spectrophotometer or set in advance.  
The correlation matrix data A of the spectral  
15 reflectance of the object 1 is also calculated from  
data measured in advance.

The matrix calculation unit 23 reads out the data  
H, A, and  $E_m$  from the storage unit 22 and calculates a  
spectral reflectance estimation matrix M for converting  
20 the RGB image data from the digital camera 3 into the  
spectral reflectance image data F.

The spectral reflectance estimation matrix M is a  
401  $\times$  3 matrix which is used to convert the RGB image  
data as three-dimensional data into a 401-dimensional  
25 spectral reflectance at the 1-nm interval in the  
wavelength range of 380 to 780 nm. Let G be the RGB  
image data output from the digital camera 3.

$$\begin{aligned} \text{Error} &= \langle (F - MG)^t (F - MG) \rangle \\ &= \langle (F - MHE_m F)^t (F - MHE_m F) \rangle \end{aligned}$$

for

$$H = \begin{pmatrix} r(380) , r(381) , \dots , r(780) \\ g(380) , g(381) , \dots , g(780) \\ b(380) , b(381) , \dots , b(780) \end{pmatrix}$$

5

$$E_m = \begin{pmatrix} E_m(380) , 0 , \dots , 0 \\ 0 , E_m(381) , \dots , 0 \\ \dots \\ 0 , 0 , \dots , E_m(780) \end{pmatrix}$$

$$F = (f(380) , f(381) , \dots , f(780))^t$$

$$M = \begin{pmatrix} m_{11} & m_{12} & m_{13} \\ m_{21} & m_{22} & m_{23} \\ \vdots & & \\ m_{4011} & m_{4012} & m_{4013} \end{pmatrix}$$

M that minimizes the above matrix is given by

$$M = A(HE_m)^t (HE_m A(HE_m)^t)^{-1}$$

for

$$A = \langle FF^t \rangle$$

10

The matrix conversion unit 21 multiplies the RGB image data G by the spectral reflectance estimation matrix M and outputs the spectral reflectance image data F.

15

FIG. 3 shows the arrangement of the tristimulus value calculation unit 5.

The tristimulus value calculation unit 5 comprises a tristimulus value matrix calculation unit 31, storage unit 32, image extraction unit 33, and tristimulus value matrix conversion unit 34.

5           The spectral reflectance image data  $F$  output from the spectral reflectance calculation unit 4 shown in FIG. 1 or 2 is input to the tristimulus value matrix calculation unit 31. A tristimulus value matrix  $M_{qc}$  is calculated on the basis of data stored in the storage  
10           unit 32.

          The tristimulus value matrix  $M_{qc}$  is input to the tristimulus value matrix conversion unit 34. The tristimulus value matrix conversion unit 34 multiplies the tristimulus value matrix  $M_{qc}$  by color chip sensing  
15           data  $P$  extracted by the image extraction unit 33 to perform matrix conversion, thereby obtaining tristimulus values  $C$ .

          The tristimulus value calculation unit 5 shown in FIG. 3 will be described in more detail. The storage  
20           unit 32 stores and holds spectral sensitivity data  $H_2$  of the second digital camera 8, color matching function data  $\underline{c}$ , and spectral reflectance data  $\underline{q}$  of the color chip 6 as data at a 1-nm interval in the wavelength range of 380 to 780 nm.

25           The tristimulus value matrix calculation unit 31 reads out the data  $H_2$ ,  $\underline{c}$ , and  $\underline{q}$  from the storage unit 32 and calculates the tristimulus value estimation

matrix  $M_{qc}$  for converting the color chip sensing data input from the second digital camera 8 through the image extraction unit 33 into the tristimulus values  $C$  under the observation illumination light spectrum of the spectral reflectance image data  $F$  read from the spectral reflectance calculation unit 4.

The image extraction unit 33 extracts data in each unit color chip region from the color chip image data  $P'$  obtained by sensing the color chip 6 with the second digital camera 8 and calculates the average signal value thereof to obtain the color chip sensing data  $P$ .

The color chip 6 is constructed by a plurality of  $(M)$  unit color chips having independent spectral reflectances. Hence,  $3M$  color chip sensing data  $P$  are obtained by sensing the  $M$  unit color chips with the digital camera 8 using three RGB channels and extracting the data by the image extraction unit 33.

The tristimulus value estimation matrix  $M_{qc}$  is a  $3 \times 3M$  matrix which is used to convert the  $3M$  color chip sensing data  $P$  obtained by the three RGB channels into the tristimulus values  $C$  as three-dimensional XYZ image data.

The tristimulus value estimation matrix  $M_{qc}$  is calculated in the following manner. Let  $h_i^{(2)}(\lambda)$  ( $i = 1$  to  $3$ ) be the spectral sensitivity data  $H2$  of the second digital camera 8,  $q_j(\lambda)$  ( $j = 1$  to  $M$ ) be the spectral reflectance data  $q$  of the color chip 6,

and  $c_i(\lambda)$  ( $i = 1$  to  $3$ ) be the color matching function data  $\underline{c}$ .

$$f'_i(\lambda) = c_i(\lambda)f(\lambda) \quad (i = 1 \sim 3)$$

$$q'_{M(i-1)+j}(\lambda) = h_i^{(2)}(\lambda)q_j(\lambda) \quad (i = 1 \sim 3, j = 1 \sim M)$$

$$f' = (f'_1, f'_2, f'_3)^t$$

$$f'_i = (f'_i(\lambda_1), f'_i(\lambda_2), \dots, f'_i(\lambda_N))$$

$$q' = (q'_1, q'_2, \dots, q'_{3M})^t$$

$$q'_i = (q'_i(\lambda_1), q'_i(\lambda_2), \dots, q'_i(\lambda_N))$$

5  $M_{qc}$  that minimizes

$$E_{qc} = (f' - M_{qc}q')^t(f' - M_{qc}q')$$

is calculated by

10 
$$M_{qc} = f'q'^t(q'q'^t)^{-1}$$

More specifically, the tristimulus value estimation matrix  $M_{qc}$  is obtained from the relationship between the product of the spectral reflectance  $f(\lambda)$  of the object 1 and the color matching functions  $c_i(\lambda)$  and the product of the spectral reflectance  $q_j(\lambda)$  of the color chip 6 and the spectral sensitivity  $h_i^{(2)}(\lambda)$  of the digital camera 8 as an input device for sensing the color chip 6.

20 The calculated tristimulus value estimation matrix  $M_{qc}$  is input to the tristimulus value matrix conversion unit 34, so the tristimulus values  $C$  are calculated by

$$C = M_{qc}P$$

$$P = (p_1, p_2, \dots, p_{3M})^t$$

$$C = (X, Y, Z)^t$$

As is apparent from equations (8), when  $E_{qc}$  is 0, accurate tristimulus values  $C$  can be obtained by the above equations for an arbitrary observation illumination light spectrum  $E_o$ . The tristimulus values  $C$  calculated by the tristimulus value matrix conversion unit 34 are input to the color image signal calculation unit 9 shown in FIG. 1.

FIG. 4 shows the arrangement of the color image signal calculation unit 9.

The color image signal calculation unit 9 comprises an output RGB matrix conversion unit 41, storage unit 42, and gray scale correction unit 43.

The tristimulus values  $C$  output from the tristimulus value matrix conversion unit 34 in the tristimulus value calculation unit 5 shown in FIG. 3 are input to the color image signal calculation unit 9. In the output RGB matrix conversion unit 41, the tristimulus values  $C$  are converted into the RGB data  $G$  by equations (9) in accordance with an output RGB matrix  $M_{cm}$  given by the storage unit 42.

$$G = M_{cm} C$$

for

$$G = (R, G, B)^t$$

$$M_{cm} = \begin{pmatrix} X_r X_g X_b \\ Y_r Y_g Y_b \\ Z_r Z_g Z_b \end{pmatrix}^{-1}$$

where  $X_r$ ,  $X_g$ , and  $X_b$  are X values for R, G, and B maximum light emission. This also applies to Y and Z values.

The RGB data G calculated by the output RGB matrix conversion unit 41 are input to the gray scale correction unit 43, and nonlinear gray scale correction is performed in accordance with gray scale correction data given by the storage unit 42.

RGB data G' (corresponding to R', G', and B' in FIG. 1) after gray scale correction are input to the CRT monitor 10 as output color image signals, and the color image of the object 1 is displayed on the CRT monitor 10.

As described above, according to the first embodiment, by using the color chip 6 having a known spectral reflectance and the digital camera 8 as an input device for sensing the color chip 6, which has a known spectral sensitivity, the spectral reflectance image data F can be converted into XYZ image data as the tristimulus values C under the observation illumination light by the tristimulus value calculation unit 5 without using any measurement instrument such as

a spectrophotometer.

If the product of the spectral reflectance  $f(\lambda)$  of the object 1 and the color matching functions  $ci(\lambda)$  can be expanded by the product of the spectral reflectance  $qj(\lambda)$  of the color chip 6 and the spectral sensitivity  $hi^{(2)}(\lambda)$  of the digital camera 8 as an input device for sensing the color chip 6, the spectral reflectance image data F can be highly accurately converted into the XYZ image data as the tristimulus values C under the observation illumination light.

In this embodiment, more accurate conversion is enabled by changing the color chip 6 to be used and the characteristics of the second digital camera 8 as an input device for sensing the color chip 6 in accordance with the spectral reflectance  $f(\lambda)$  of the object 1.

(Second Embodiment)

FIG. 5 shows a color reproduction system according to the second embodiment of the present invention.

In this embodiment, the output from a spectral reflectance calculation unit 14 becomes the expansion coefficient when the spectral reflectance of an object 1 is represented as the linear sum of basis functions. The arrangement of this embodiment is the same as that described in the first embodiment except the spectral reflectance calculation unit 14 and tristimulus value calculation unit 15, and a detailed description thereof will be omitted.



The spectral reflectance calculation unit 14 receives RGB image data from a digital camera 3 and outputs expansion coefficient data K when the spectral reflectance of the object 1 is represented by the linear sum of basis functions by using the spectral sensitivity data of the digital camera 3, spectrum data of sensing illumination light, and statistic data of the spectral reflection of the object 1.

The expansion coefficient data K is input to the tristimulus value calculation unit 15. The tristimulus value calculation unit 15 also receives color chip image data P' corresponding to a color chip 6, which is output from a second digital camera 8 as an input device which senses the color chip 6 formed from a plurality of unit color chips under observation illumination light by observation illumination 7.

On the basis of the expansion coefficient data K input from the spectral reflectance calculation unit 14, the color chip image data P' output from the second digital camera 8, the spectral sensitivity data of the digital camera 8, the spectral reflectance data of the color chip 6, and the color matching function data, the tristimulus value calculation unit 15 calculates tristimulus values X, Y, and Z corresponding to the spectral reflectance of the object 1 under the observation illumination light and inputs the XYZ image data to a color image signal calculation unit 9.

The spectral sensitivity of the digital camera 8, the color chip spectral reflectance, and color matching functions have known values, and these data are stored and held in the tristimulus value calculation unit 15 in advance.

FIG. 6 shows the arrangement of the spectral reflectance calculation unit 14. The spectral reflectance calculation unit 14 comprises a matrix conversion unit 61, storage unit 62, and matrix calculation unit 63.

The RGB image data from the first digital camera 3 are input to the matrix conversion unit 61. The RGB data are multiplied by a matrix calculated by the matrix calculation unit 63 on the basis of data stored in the storage unit 62, so the expansion coefficient data K of the spectral reflectance is output.

The storage unit 62 stores and holds spectral sensitivity data H of the first digital camera 3, correlation matrix data A' of the expansion coefficient when the spectral reflectance of the object 1 is represented as the linear sum of basis functions, basis function data V of the spectral reflectance of the object 1, and sensing illumination light spectrum data Em as data at a 1-nm interval in the wavelength range of 380 to 780 nm.

The matrix calculation unit 63 reads out the data H, A', V, and Em from the storage unit 62 and

calculates a expansion coefficient estimation matrix  $M$  for converting the RGB image data from the digital camera 3 into the expansion coefficient data  $K$  of the object spectral reflectance.

5           The expansion coefficient estimation matrix  $M$  is an  $R \times 3$  matrix which is used to convert the three-dimensional RGB data into a expansion coefficient related to  $R$  basis functions. Let  $G$  be the RGB image data from the digital camera 3.

10

$$\begin{aligned} \text{Error} &= \langle (K - MG)^t (K - MG) \rangle \\ &= \langle (K - MHE_m F)^t (K - MHE_m F) \rangle \\ &= \langle (K - MHE_m VK)^t (K - MHE_m VK) \rangle \end{aligned}$$

for

$$H = \begin{pmatrix} r(380) , r(381) , \dots , r(780) \\ g(380) , g(381) , \dots , g(780) \\ b(380) , b(381) , \dots , b(780) \end{pmatrix}$$

$$E_m = \begin{pmatrix} E_m(380) , 0 , \dots , 0 \\ 0 , E_m(381) , \dots , 0 \\ \dots \\ 0 , 0 , \dots , E_m(780) \end{pmatrix}$$

$$V = \begin{pmatrix} v_1(380)v_2(380) \dots v_R(380) \\ v_1(381)v_2(381) \dots v_R(381) \\ \dots \\ v_1(780)v_2(780) \dots v_R(780) \end{pmatrix}$$

$$K = (k_1, k_2, \dots, k_R)^t$$

$$M = \begin{pmatrix} m_{11} & m_{12} & m_{13} \\ m_{21} & m_{22} & m_{23} \\ \vdots & & \\ m_{R1} & m_{R2} & m_{R3} \end{pmatrix}$$

M that minimizes the above matrix is given by

$$M = \langle K^t K \rangle (H E_m V)^t (H E_m V \langle K^t K \rangle (H E_m V)^t)^{-1}$$

The matrix conversion unit 61 multiplies the RGB image data G by the calculated expansion coefficient estimation matrix M, thereby outputting the expansion coefficient data K.

FIG. 7 shows the arrangement of the tristimulus value calculation unit 15. The tristimulus value calculation unit 15 comprises an image extraction

unit 71, tristimulus value matrix calculation unit 72, storage unit 73, and tristimulus value matrix conversion unit 74.

5       The color chip image data  $P'$  obtained by sensing the color chip 6 with the digital camera 8 is input to the tristimulus value matrix calculation unit 72 through the image extraction unit 71. A tristimulus value estimation matrix  $M_{qc}$  is calculated on the basis of data stored in the storage unit 73.

10       The tristimulus value estimation matrix  $M_{qc}$  is input to the tristimulus value matrix conversion unit 74. In the tristimulus value matrix conversion unit 74, the tristimulus value estimation matrix  $M_{qc}$  is multiplied by the expansion coefficient data  $K$  of the spectral reflectance of the object 1, which is output from the spectral reflectance calculation unit 14, thereby obtaining tristimulus values  $C$ .

20       Each section shown in FIG. 7 will be described in more detail. The storage unit 73 stores and holds spectral sensitivity  $H_2$  of the second digital camera 8, color matching function data  $\underline{c}$ , spectral reflectance data  $g$  of the color chip 6, and basis function data  $V$  of the object spectral reflectance as data at a 1-nm interval in the wavelength range of 380 to 780 nm.

25       The tristimulus value matrix calculation unit 72 reads out the data  $H_2$ ,  $\underline{c}$ ,  $g$ , and  $V$  from the storage unit 73 and calculates the tristimulus value estimation

matrix  $M_{qc}$  for converting color chip sensing data  $P$  input from the second digital camera 8 through the image extraction unit 71 into the tristimulus values  $C$  under the observation illumination light of the spectral reflectance corresponding to the expansion coefficient of the expansion coefficient data  $K$  read from the spectral reflectance calculation unit 14.

The image extraction unit 71 extracts data in each unit color chip region from the color chip image data  $P'$  obtained by sensing the color chip 6 with the second digital camera 8 and calculates the average signal value, thereby obtaining the color chip sensing data  $P$ .

The color chip 6 is constructed by a plurality of  $(M)$  unit color chips having independent spectral reflectances. Hence,  $3M$  color chip sensing data  $P$  are obtained by sensing the  $M$  unit color chips with the digital camera 8 using three RGB channels and extracting the data by the image extraction unit 71.

The tristimulus value estimation matrix  $M_{qc}$  is a  $3 \times R$  matrix which is used to convert the  $R$  expansion coefficient data  $K$  into the tristimulus values  $C$  as three-dimensional XYZ image data. The tristimulus value estimation matrix  $M_{qc}$  is calculated in the following manner. Let  $h_i^{(2)}(\lambda)$  ( $i = 1$  to  $3$ ) be the spectral sensitivity data  $H2$  of the digital camera 8 as an input device,  $q_j(\lambda)$  ( $j = 1$  to  $M$ ) be the spectral reflectance data  $q$  of the color chip 6,  $c_i(\lambda)$  ( $i = 1$

to 3) be the color matching function data  $c_l$ ,  $V_l(\lambda)$  and  $k_l$  ( $l = 1$  to  $R$ ) be the basis function  $V$  and expansion coefficient  $K$  of the spectral reflectance of the object 1, respectively.

5

$$f(\lambda) = \sum_{l=1}^R k_l v_l(\lambda)$$

$$f'_{i1}(\lambda) = c_i(\lambda) v_l(\lambda) \quad (i = 1 \sim 3, l = 1 \sim R)$$

$$q'_{M(i-1)+j}(\lambda) = h_i^{(2)}(\lambda) q_j(\lambda) \quad (i = 1 \sim 3, j = 1 \sim M)$$

$$f'^{(1)} = (f'_{11}, f'_{21}, f'_{31})^t$$

$$f'_{i1} = (f'_{i1}(\lambda_1), f'_{i1}(\lambda_2), \dots, f'_{i1}(\lambda_N))$$

$$q' = (q'_1, q'_2, \dots, q'_{3M})^t$$

$$q'_i = (q'_i(\lambda_1), q'_i(\lambda_2), \dots, q'_i(\lambda_N))$$

$M^{(1)}_{qc}$  that minimizes

$$E^{(1)}_{qc} = (f'_1 - M^{(1)}_{qc} q')^t (f'_1 - M^{(1)}_{qc} q')$$

10

is calculated by

$$M^{(1)}_{qc} = f'_1 q'^t (q' q'^t)^{-1}$$

The tristimulus values  $C^{(1)}$  of the basis functions are obtained by

15

$$C^{(1)} = M^{(1)}_{qc} P$$

$$P = (p_1, p_2, \dots, p_{3M})^t$$

$$C^{(1)} = (X^{(1)}, Y^{(1)}, Z^{(1)})^t$$

The tristimulus value estimation matrix  $M_{qc}$  is given by

$$M_{qc} = (C^{(1)}, C^{(2)}, \dots, C^{(R)})$$

20

More specifically, the tristimulus value

estimation matrix  $M_{qc}$  is obtained as the linear sum of the tristimulus values  $C^{(1)}$  of the basis functions, which is obtained by multiplying the color chip sensing data  $P$  by a matrix  $M^{(1)}_{qc}$  obtained from the relationship between the product of a plurality of basis functions  $v_l(\lambda)$  for the spectral reflectance  $f(\lambda)$  of the object 1 and the color matching functions  $ci(\lambda)$  and the product of the spectral reflectance  $qj(\lambda)$  of the color chip 6 and the spectral sensitivity  $hi^{(2)}(\lambda)$  of the digital camera 8 as an input device for sensing the color chip 6.

The calculated tristimulus value estimation matrix  $M_{qc}$  is input to the tristimulus value matrix conversion unit 74 and converted into the tristimulus values  $C$  by

$$C = M_{qc}K$$

As is apparent from equation (18), when  $E^{(1)}_{qc}$  ( $l = 1$  to  $R$ ) is 0, accurate tristimulus values  $C$  can be obtained by the above equations for an arbitrary observation illumination light spectrum  $E_o$ .

The tristimulus values  $C$  calculated by the tristimulus value matrix conversion unit 74 are input to the color image signal calculation unit 9 shown in FIG. 5, converted into RGB data as output color image signals, and input to a CRT monitor 10, as in the first embodiment. The arrangement of the color image signal calculation unit 9 is the same as in the first embodiment, and a detailed description thereof will be



omitted.

As described above, according to the second embodiment, by using the color chip 6 having a known spectral reflectance and the digital camera 8 as an input device for sensing the color chip 6, which has a known spectral sensitivity, the spectral reflectance image data F can be converted into XYZ image data as the tristimulus values C under the observation illumination light by the tristimulus value calculation unit 15 without using any measurement instrument such as a spectrophotometer, as in the first embodiment.

If the product of the plurality of basis functions  $v_1(\lambda)$  of the spectral reflectance  $f(\lambda)$  of the object 1 and the color matching functions  $ci(\lambda)$  can be expanded by the product of the spectral reflectance  $qj(\lambda)$  of the color chip 6 and the spectral sensitivity  $hi^{(2)}(\lambda)$  of the digital camera 8 as an input device for sensing the color chip 6, the spectral reflectance image data F can be highly accurately converted into the XYZ image data as the tristimulus values C under the observation illumination light.

In this embodiment, more accurate conversion is enabled by changing the color chip 6 to be used and the characteristics of the second digital camera 8 as an input device for sensing the color chip 6 in accordance with the basis functions V of the spectral reflectances  $f(\lambda)$  of the object 1.

According to this embodiment, since all of the spectral reflectances  $f(\lambda)$  of the object 1 are expanded by the basis functions  $V$ , the conversion accuracy for the actual object 1 can be obtained in advance by  
5 evaluating the conversion accuracy for the basis function  $V$  in advance.

In this embodiment, the tristimulus values  $C^{(1)}$  under the observation illumination light corresponding to the basis function  $V$  of the spectral reflectance  
10  $f(\lambda)$  of the object 1 can be calculated in advance. For this reason, after the expansion coefficient  $K$  corresponding to the spectral reflectance  $f(\lambda)$  is input, the tristimulus values  $C$  under the observation illumination light corresponding to the spectral  
15 reflectance  $f(\lambda)$  can be calculated at a high speed as the linear sum of the tristimulus values  $C^{(1)}$  of the basis functions.

(Other Embodiments)

The present invention is not limited to the above  
20 embodiments, and various changes and modifications can be made.

(1) In the first and second embodiments, the spectral reflectance  $f(\lambda)$  of the object 1 is calculated from image data obtained by sensing the object 1 with  
25 the digital camera 3. However, the present invention is not limited to this, and the spectral reflectance image data of an arbitrary object can be used.

(2) In the first and second embodiments, the CRT monitor 10 has been exemplified as the color image output means. However, this can be replaced with an image output device such as a display of another scheme or a printer.

(3) In the first and second embodiments, the digital camera 8 with three RGB channels is used as the input device for sensing the color chip 6. However, for the camera for sensing the color chip 6, an arbitrary spectral sensitivity characteristic and an arbitrary number of channels can be selected.

(4) In the present invention, a system may be constructed in which the sensing side for sensing the object 1 is located in a remote site separated from the observation side for observing an object image displayed on the CRT monitor 10, and image data is transmitted.

In this case, the spectral reflectance calculation unit 4 or 14, tristimulus value calculation unit 5 or 15, and color image signal calculation unit 9 can be provided either on the sensing side or on the observation side.

In this case, the processing described in the above embodiments can be realized by storing data necessary for processing by the spectral reflectance calculation unit 4 or 14, tristimulus value calculation unit 5 or 15, and color image signal calculation unit 9

in the respective units or acquiring the data by transmission.

(5) In the first embodiment, the tristimulus values  $C$  under the observation illumination light of the object 1 are obtained assuming that the product of the spectral reflectance  $f(\lambda)$  of the object 1 and the color matching functions  $ci(\lambda)$  can be expanded by combining the spectral reflectance  $qj(\lambda)$  of the color chip 6 and the spectral sensitivity  $hi^{(2)}(\lambda)$  of the digital camera 8 for sensing the color chip 6. Even when the spectral reflectance  $f(\lambda)$  of the object 1 can be expanded by a value obtained by dividing the product of the spectral reflectance  $qj(\lambda)$  of the color chip 6 and the spectral sensitivity  $hi^{(2)}(\lambda)$  of the digital camera 8 by the color matching functions  $ci(\lambda)$ , the tristimulus values  $C$  under the observation illumination light of the object can be obtained.

In this case, when the spectral reflectance  $f(\lambda)$  of the object 1 is multiplied by a matrix, the spectral reflectance can be converted into the tristimulus values  $C$  under the observation illumination light. By coupling a matrix used to calculate the spectral reflectance  $f(\lambda)$  from the object image signal obtained by sensing the object 1 with the digital camera 3, the object image signal can be directly converted into the tristimulus values  $C$  under the observation illumination light.

The present invention is not limited to the method of calculating the tristimulus values under the observation illumination light from the spectral reflectance of the object and also incorporates a method of directly calculating the tristimulus values under the observation illumination light from the signal value obtained by an input device such as a camera.

(6) As a modification to the second embodiment, the tristimulus values  $C$  under the observation illumination light can be directly calculated from the object image signal by coupling a matrix for calculating the expansion coefficient  $K$  of the basis function  $V$  of the spectral reflectance  $f(\lambda)$  of the object 1 from the object image signal obtained by sensing the object to a matrix for calculating the tristimulus values  $C$  under the observation illumination light of the object 1 from the expansion coefficient. The present invention also incorporates such a substantially equivalent processing method.

As has been described above, according to the present invention, a color reproduction system having a color image processing apparatus for easily converting the spectral reflectance image of an object into a tristimulus image under observation illumination light without using any measurement instrument such as a spectrophotometer can be provided.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the invention in its broader aspects is not limited to the specific details and representative embodiments shown and described herein. Accordingly, various  
5 modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.

WHAT IS CLAIMED IS:

1. A color reproduction system comprising:  
tristimulus value calculation means for  
calculating tristimulus values under observation  
5 illumination light corresponding to a spectral  
reflectance of an object, said tristimulus value  
calculation means calculating the tristimulus values  
using spectral reflectance data of a color chip formed  
from a plurality of unit color chips, color chip  
10 sensing data obtained by sensing the color chip with an  
input device under the observation illumination light,  
spectral sensitivity data of said input device, and  
color matching function data;  
means for calculating an output color image signal  
15 based on the calculated tristimulus values; and  
means for outputting a color image based on the  
output color image signal.
2. A system according to claim 1, wherein said  
tristimulus value calculation means multiplies the  
20 color chip sensing data by a matrix obtained from  
a relationship between a product of the spectral  
reflectance of the object and color matching functions  
and a product of the spectral reflectance data of the  
color chip and the spectral sensitivity of said input  
25 device, thereby calculating the tristimulus values.
3. A system according to claim 1, wherein said  
tristimulus value calculation means obtains the

tristimulus values as a linear sum of basis function  
tristimulus values obtained by multiplying the color  
chip sensing data by a matrix obtained from a  
relationship between a product of a plurality of basis  
5 functions of the spectral reflectance of the object and  
color matching functions and a product of the spectral  
reflectance data of the color chip and the spectral  
sensitivity of said input device.

4. A system according to claim 1, wherein each of  
10 said first image sensing means and said second image  
sensing means comprises a digital camera.

5. A system according to claim 1, wherein the  
color chip has a plurality of unit color chips having  
independent spectral reflectances and arrayed in a  
15 matrix.

6. A system according to claim 1, wherein said  
means for outputting the color image comprises a  
monitor, and said means for outputting the output color  
image calculates the output color image on the basis of  
20 characteristics of said monitor.

7. A color reproduction system comprising:  
first image sensing means for sensing an object  
under sensing illumination light;

means for calculating a spectral reflectance of  
25 image data of the object sensed by said first image  
sensing means on the basis of spectral sensitivity data  
of said first image sensing means, spectrum data of



the sensing illumination light, statistic data of a spectral reflectance of the object, and outputting spectral reflectance image data corresponding to the calculated spectral reflectance;

5           second image sensing means for sensing a color chip under observation illumination light;

          means for calculating tristimulus values of the object under the observation illumination light on the basis of the output spectral reflectance image data, color chip image data of the color chip sensed by said  
10           second image sensing means, spectral sensitivity data of said second image sensing means, color chip spectral reflectance data representing a spectral reflectance distribution of the color chip, and color matching  
15           function data;

          means for calculating an output color image signal on the basis of the calculated tristimulus values; and

          means for outputting a color image on the basis of the output color image signal.

20           8. A system according to claim 7, wherein each of said first image sensing means and said second image sensing means comprises a digital camera.

          9. A system according to claim 7, wherein the color chip has a plurality of unit color chips having  
25           independent spectral reflectances and arrayed in a matrix.

          10. A system according to claim 7, wherein said

means for outputting the color image comprises a monitor, and said means for outputting the output color image calculates the output color image on the basis of characteristics of said monitor.

5           11. A color reproduction system comprising:

          first image sensing means for sensing an object under sensing illumination light;

          means for outputting expansion coefficient data which is represented as a linear sum of basis functions  
10       of a spectral reflectance of the object on the basis of spectral sensitivity data of said first image sensing means, spectrum data of the sensing illumination light and statistic data of a spectral reflectance of the object;

15           second image sensing means for sensing a color chip under observation illumination light;

          means for calculating tristimulus values of the object under the observation illumination light on the basis of the output expansion coefficient data, color  
20       chip image data of the color chip sensed by said second image sensing means, spectral sensitivity data of said second image sensing means, color chip spectral reflectance data representing a spectral reflectance distribution of the color chip, and color matching  
25       function data;

          means for calculating an output color image signal on the basis of the calculated tristimulus values; and

means for outputting a color image on the basis of the output color image signal.

12. A system according to claim 11, wherein each of said first image sensing means and said second image sensing means comprises a digital camera.

13. A system according to claim 11, wherein the color chip has a plurality of unit color chips having independent spectral reflectances and arrayed in a matrix.

14. A system according to claim 11, wherein said means for outputting the color image comprises a monitor, and said means for outputting the output color image calculates the output color image on the basis of characteristics of said monitor.

ABSTRACT OF THE DISCLOSURE

A color reproduction system includes a tristimulus value calculation unit for calculating tristimulus values (X, Y, Z) under observation illumination light corresponding to the spectral reflectance of an object, which is obtained by a spectral reflectance calculation unit, and a color image signal calculation unit for calculating output color image signals (R', G', B') to a CRT monitor on the basis of the tristimulus values (X, Y, Z). The tristimulus value calculation unit converts spectral reflectance image data (F) of the object into tristimulus value image data (X, Y, Z) under the observation illumination light using the spectral reflectance data of a color chip formed from a plurality of unit color chips, color chip image data (P') obtained by sensing the color chip with a digital camera under the observation illumination light, spectral sensitivity data of the digital camera, and color matching function data.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

# Declaration Power of Attorney For Patent Application

## 特許出願宣言書及び委任状 Japanese Language Declaration

日本語宣言書

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の横に記載された通りです。

My residence, post office address and citizenship are as stated below next to my name,

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

色再現システム

COLOR REPRODUCTION SYSTEM

上記発明の明細書（下記の欄で×印がついていない場合は、本書に添付）は、

The specification of which is attached hereto unless the following box is checked:

☐ \_\_\_\_\_月 \_\_\_\_\_日に

提出され米国出願番号または特許協定条約

☐ was filed on \_\_\_\_\_  
as United States Application Number or  
PCT international Application Number

国際出願番号を \_\_\_\_\_ とし、

（該当する場合） \_\_\_\_\_ 月 \_\_\_\_\_ 日に訂正されました。

\_\_\_\_\_ and was amended on

\_\_\_\_\_ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されたとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56



## Japanese Language Declaration

(日本語宣言書)

私は、合衆国法典第35編第119条(a)-(d)項又は第365条(b)に基づき下記の、米国以外の国の少なくとも一カ国を指定している特許協力条約365(a)項に基づく国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

I hereby claim foreign priority under Title 35, United States Code, Section 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT international application having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)  
外国での先行出願

Priority Not Claimed  
優先権の主張なし

11-144932 (Number) (番号)	JAPAN (Country) (国名)	25/05/1999 (Day/Month/Year Filed) (出願年月日)	<input type="checkbox"/>
_____	_____	_____	<input type="checkbox"/>
_____	_____	_____	<input type="checkbox"/>
_____	_____	_____	<input type="checkbox"/>
_____	_____	_____	<input type="checkbox"/>

私は、第35編米国法典119条(e)項に基づいて下記の米国特許出願規定に記載された権利をここに主張いたします。

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.) (出願番号)	(Filing Date) (出願日)	(Application No.) (出願番号)	(Filing Date) (出願日)
-----------------------------	------------------------	-----------------------------	------------------------

私は、下記の米国法典第35編120条に基づいて下記の米国特許出願に記載された権利、又は米国を指定している特許協力条約365条(c)に基づき権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国特許出願に開示されていない限り、その先行米国出願書提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) or 365(c) of any PCT international application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT Information application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which become available between the filing date of the prior application and the national or PCT international filing date of application:

(Application No.) (出願番号)	(Filing Date) (出願日)	(Status: Patented, Pending, Abandoned) (現況: 特許許可済、係属中、放棄済)
_____	_____	_____
(Application No.) (出願番号)	(Filing Date) (出願日)	(Status: Patented, Pending, Abandoned) (現況: 特許許可済、係属中、放棄済)

私は、私自身の知識に基づいて本宣言書中で私が行う表明が真実であり、かつ私の入手した情報と私の信じることに基づき、かつ表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の声明を行えば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

## Japanese Language Declaration

(日本語宣言書)

委任状：私は、下記の発明者として、本出願に関する一切の手続きを米特許商標局に対して遂行する弁理士または代理人として、下記の者を指名いたします。  
(弁理士、または代理人の氏名及び登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)

John C. Pokotylo (Reg. No. 36,242) and Michael P. Straub (Reg. No. 36,941)

書類送付先：

Send Correspondence to  
STRAUB & POKOTYLO

1 Bethany Road  
Suite 56, Bldg. 4  
Hazlet, NJ 07730

直通電話連絡先：

Direct Telephone Calls to: (name and telephone number)  
Telephone No. (732) 335-1222  
Facsimile No. (732) 335-1228

唯一のまたは第一発明者の氏名 大澤 健郎	Full name of sole or first inventor Kenro Ohsawa
同発明者の署名 日付	Inventor's signature Date <i>Kenro Ohsawa May 17, 2000</i>
住 所 日本国武蔵野市	Residence Musashino-shi, Japan
国 籍 日本	Citizenship JAPAN
郵便の宛先 日本国東京都八王子市久保山町2-3	Post Office Address c/o Intellectual Property Department, OLYMPUS OPTICAL CO., LTD.
オリンパス光学工業株式会社 知的財産部内	2-3, Kuboyama-cho, Hachioji-shi, Tokyo, Japan

(第二以降の共同発明者に対しても同様に記載し、署名をすること。)

(Supply similar information and signature for second and subsequent joint inventors.)